

(12) INTERNATIONAL PUBLICATION PUBLISHED IN PURSUANCE OF THE  
PATENT COOPERATION TREATY (PCT)

- (19) World Organization of Intellectual Property International Bureau [WIPO] PCT (10) International Publication No.: **WO 2004/030170 A2**
- (43) International publication date: April 8, 2004  
(4/8/2004)
- 

- (51) International patent classification<sup>7</sup>: H 02 B 1/044
- (21) International application number: PCT/FR2003/050050
- (22) International filing date: September 11, 2003 (9/11/2003)
- (25) Filing language: French
- (26) Publication language: French
- (30) Data relative to priority:  
02 11807 September 24, 2002 (9/24/2002) FR
- (71) Applicant: *(for all designated states except US)*: FCI  
[FR/FR]; 145 rue Yves Le Coz, F-78000 VERSAILLES (FR)
- (72) Inventors; and
- (75) Inventors/Applicants *(only for US)*: BISSON, Didier [FR/FR]; 28, rue des Oréades, F-25300 DOUBS (FR). CHANTREL, Philippe [FR/FR]; 13, rue Arago, F-25300 PONTARLIER (FR). MOUGIN, Franck [FR/FR]; 12, rue des Charmilles, F-25300 DOMMARTIN (FR).
- (74) Agent: SCHMIT, Christian, Norbert,; SCHMIT CHRETIEN SCHIHIN, 8 place du Ponceau, F-95000 CERGY (FR).
- (81) Designated states *(national)*: CN, US
- (84) Designated states *(regional)*: European Patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR).

**Published:**

-- without International Search Report, will be published again when this report is received.

*With regard to the two-letter country codes and other abbreviations, refer to the "Explanatory notes relating to codes and abbreviations" at the beginning of each regular issue of the PCT Gazette.*

(54) Title: BUS BAR FASTENING AND CONTACT DEVICE

(57) Abstract:

Fastening and contact device (1) to be mounted on a plate (2) provided with bus bars, said device comprising a sleeve (5) and a ring (6) to be mounted through an opening (3) of the plate. The sleeve comprises shoulders (7) that come to rest on a first side (4) of the plate, while the ring slides along the sleeve until it comes into contact with a second side (10) of the plate. The plate is clamped between the sleeve and the ring when a tightening means (13) cooperates with the sleeve and a complementary device (14) to which the plate is connected.

